

standard flags

direct web link:
www.tobermore.co.uk/pavingflags

sales & technical line:
028 7964 2411
(for ROI change 028 to 048)

nbsPlus Q25 31 315

Tobermore's extensive Standard Flag range has been a recognised choice for customers over many years. This flag range has a tough durable surface finish and is suitable for a wide range of domestic and commercial applications.



The Standard Flag range is available in various sizes and in four standard colours, giving the designer increased choice for each scheme.

product specifications

Manufactured to	BS EN 1339:2003
Product type	Concrete paving flag
Installed to	BS EN 7533-4:2006
Applications	Residential and commercial
Complementary paving	Tegula Setts & Circle, Mayfair Setts & Circle
Complementary kerbs	Kerbsett, Kerbstone, Country Kerb

Tobermore operate an Integrated Management System and is an accredited ISO9001:2000 and ISO14001:2004 company.

colours



product information

product	size (mm)	finish	edge	colours available	in stock	no. per m ²	no. per bale	weight (kg) per bale	full load 8wh	full load 40ft
STANDARD FLAGS	900 x 600 x 63	DIMPLED OR TEXTURED	SQUARE	Natural	YES	1.85	16	1300	224	320
	900 x 600 x 50	DIMPLED	SQUARE	Natural	YES	1.85	20	1300	280	400
	600 x 600 x 63	DIMPLED	SQUARE	Natural	YES	2.78	16	860	336	480
	600 x 600 x 50	DIMPLED	SQUARE	Natural	YES	2.78	20	860	420	600
	600 x 600 x 50	PATIO NON-SLIP	CHAMFERED	Natural, Red, Charcoal, Golden	YES	2.78	20	860	420	600
	600 x 450 x 50	DIMPLED	SQUARE	Natural	YES	3.70	20	650	560	800
	450 x 450 x 70	DIMPLED	CHAMFERED	Natural	MADE TO ORDER	4.94	15	500	540	780
	450 x 450 x 50	DIMPLED	CHAMFERED	Natural Charcoal & Buff made to order	YES	4.94	20	500	720	1040
	400 x 400 x 65	NON-SLIP SMOOTH	CHAMFERED	Natural, Red, Charcoal, Golden	MADE TO ORDER	6.25	16	400	720	1040
	400 x 400 x 50	NON-SLIP SMOOTH	CHAMFERED	Natural Red, Charcoal & Golden made to order	YES	6.25	20	400	900	1300
	400 x 400 x 40	NON-SLIP SMOOTH	CHAMFERED	Natural, Red, Charcoal, Golden	YES	6.25	25	370	1225	1750

See instructions and warnings on page 146.