

Braemar

ground | ground textured

- Premium block paving
- Manufactured with natural granite aggregates†
- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Creates a striking, contemporary look
- Readily available with much shorter lead times than natural stone
- Cost-effective alternative to natural stone

NEW!



Block Paving

product specifications

Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Surface Layer	Hard wearing surface layer with a minimum of 4mm and >390kgs/m ³ cement
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Typical tensile splitting strength of >3.6MPa
Slip/Skid Risk	Low
Installed to	(Externally) BS 7533-3:2005 (Internally) Details available on request
BS	Plus: Q24 110 Create: 45-20 64/400
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 10%
Carbon Footprint	34kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breem rating www.bre.co.uk	B , according to the Green Guide to Specification, 4 th Edition 2009. A , can be achieved when used in conjunction with a prepared recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016 and BES 6001.



FM 11763 EMS 88400



colours



Important Slip/skid Information

A regular maintenance programme should always be established and active for all public spaces to reduce the risk of slip/skid. Tobermore's stunning ground and ground textured finishes are created using a modern diamond grinding process which achieves a premium finish. Ground textured provides a higher level of slip resistance.

Important Information

Tobermore recommend that you separate product groups using contrasting bands of colour as each product is manufactured separately and may have slight variations in colour.

product	size (mm)	edge	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight (kg) per pack
BRAEMAR GROUND & GROUND TEXTURED 80MM	200 x 100 x 80	SQUARE EDGE	Alto Silver, Cara Slate, Innis Black	YES	9.6	1.6	50	480	1756
			Arran Stone, Iona White, Islay Rose, Jura Grey, Persa Blue	SPECIAL ORDER					
	300 x 200 x 80	SQUARE EDGE	Alto Silver, Cara Slate, Innis Black	YES	9.6	2.4	16.66	160	1756
			Arran Stone, Iona White, Islay Rose, Jura Grey, Persa Blue	SPECIAL ORDER					
	300 x 300 x 80	SQUARE EDGE	Alto Silver, Cara Slate, Innis Black	YES	7.2	1.8	11.11	80	1319
			Arran Stone, Iona White, Islay Rose, Jura Grey, Persa Blue	SPECIAL ORDER					
	600 x 300 x 80	SQUARE EDGE	Alto Silver, Cara Slate, Innis Black	YES	7.2	3.6	5.55	40	1319
			Arran Stone, Iona White, Islay Rose, Jura Grey, Persa Blue	SPECIAL ORDER					

*Ordering Information

Minimum order of 250 m² for Arran Stone, Iona White, Islay Rose, Jura Grey and Persa Blue

Refer to all instructions and warnings on our website

visit www.tobermore.co.uk | call us 0844 800 5736 | follow us

02J18