



Declaration of Performance for:

BLOCK PAVING

City Pave VS5 / Fusion / Manhattan Mixed Size / Pedesta / Retro / Sienna / Shannon / Sienna Setts / Tegula
Tegula Setts / Hydropave Block Paving / Braemar / Artro / Air Clean Fusion / Marker blocks

Intended Use: External pedestrian and vehicular areas subject to appropriate sub-base design

This declares that the stated product range complies with the highest requirements of the
European standard BS EN 1338:2003

This declaration is awarded the following tests carried out on samples on the stated product range.

Essential Requirements	Declared Performance	Technical specification
Dimensions	As per tables 1,2,3	EN 1338 – 5.2.4
Tensile splitting strength	Up to 50mm depth $\geq 3.5\text{MPa}$ Greater than 50mm 5MPa (Class 3)	EN 1338 – 5.3.3.2
Emission of asbestos	None	EN 1338 – 4.2
Slip / Skid resistance	USRV >45 PSRV >45	EN 1338 -5.3.5.3
Durability (against freeze/thaw)	$\leq 1.0 \text{ kg/m}^2$ as a mean with no individual value $> 1.5 \text{ kg/m}^2$ Class 3	EN 1338 – 5.3.2.2
Reaction to fire	Class A1	EN 1338 – 5.3.6.1
External Fire	Deemed to satisfy when used for roofing	EN 1338 – 5.3.6.1
Abrasion Resistance	$\leq 23\text{mm}$ (Wide Wheel Abrasion Test) Class 3	EN 1338 – 5.3.4.2
Note: Refer to the Tobermore Paving & Walling Specification Guide for comprehensive product details		

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the above Standard when installed in accordance with Tobermore's guidelines

Signed: _____

Full Name: David Henderson

Position: Owner & Managing
Director, Tobermore

Date: January 2024

This declaration is the responsibility of the manufacturer:

Tobermore Head Office

2 Lisnamuck Road, Tobermore, County L'derry, BT45 5QF

Tel: NI: 028 7964 2411 | GB: 0844 800 5736