



Declaration of Performance for:

LANSDOWNE FACING BRICK

Intended Use: Facing masonry unit for use as external walls, in load bearing or non-load bearing building and civil engineering applications.

This declares that the stated product range complies with the highest requirements of the
European standard BSEN 771-3:2011+A1:2015

This declaration is awarded the following tests carried out on samples on the stated product range.

Essential Characteristic	Declared Performance
Dimensions	L x W x H = 215 x 100 x 65 mm
Configuration	Group 1
Tolerance Category	D2
Mean Compressive Strength	22.0 N/mm ²
Direction of load	Perpendicular to bed faces
Unit Category	Category 1
Moisture Movement	<0.6 mm/m
Shear Bond Strength	0.15 N/mm ²
Flexural Bond Strength	NPD
Reaction to Fire	A1
Water Absorption	2.9 g / (m ² x s) V
Water Vapour Permeability	5/15µ
Direct Airborne Sound Insulation - Gross density	1900 kg/m ³
Thermal Resistance	Protected 1.59W/mK Exposed 1.70W/mK
Note: Refer to the Tobermore Paving & Walling Specification Guide for comprehensive product details	

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the above Standard when installed in accordance with Tobermore's guidelines

Signed: 

Full Name: David Henderson
Position: Owner & Managing
Director, Tobermore
Date: January 2024

This declaration is the responsibility of the manufacturer:
Tobermore Head Office
2 Lisnamuck Road, Tobermore, County L'derry, BT45 5QF
Tel: NI: 028 7964 2411 | GB: 0844 800 5736