

(€ Declaration of Performance for:

PAVING FLAGS

Beaufort Flags / Historic Flags / Mayfair Flags / Riven Flags / Textured Flags / Classica Flags / Tactile Flags / Hydropave Flags Manhattan 600x150x80mm / Granite Step Units / Mayfair Step Flags / Braemar 600x300mm / Fusion 600x300mm / Turfstone*

Intended Use: External pedestrian and vehicular areas subject to appropriate sub-base design

This declares that the stated product range complies with the highest requirements of the **European standard BS EN 1339:2003**

This declaration is awarded the following tests carried out on samples on the stated product range.

Essential Requirements	Declared Performance	Technical specification
Dimensions	As per tables 1,2,3	EN 1339 - 5.2.4
Breaking Strength	Up to 50mm depth ≥ 3.5MPa Greater than 50mm 5MPa (Class 3) *Turfstone 2.9 MPa	EN 1339 - 5.3.3.2
Emission of asbestos	None	EN 1339 - 4.2
Slip/skid risk	USRV >45 PSRV >45	EN 1339 -5.3.5.3
Durability (against freeze/thaw)	≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m² Class 3	EN 1339 - 5.3.2.2
Reaction to fire	Class A1	EN 1339 - 5.3.7.1
External Fire	Deemed to satisfy when used for roofing	EN 1339 - 5.3.7.1
Abrasion Resistance	≤ 23mm (Wide Wheel Abrasion Test) Class 3	EN 1339 - 5.3.4.2
Note: Refer to the Tobermore Paving & Walling Specification Guide for comprehensive product details		

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the above Standard when installed in accordance with Tobermore's guidelines

Signed:

Full Name: David Henderson **Position:** Owner & Managing

Director, Tobermore **Date:** January 2024

This declaration is the responsibility of the manufacturer:

Tobermore Head Office

2 Lisnamuck Road, Tobermore, County L'derry, BT45 5QF **Tel:** NI: 028 7964 2411 | GB: 0844 800 5736