



Declaration of Performance for:

SECURA WALLING

Secura Lite

Intended Use: Retaining wall system for domestic and commercial applications when designed and constructed in strict accordance with Tobermore guidelines. Maximum retained gravity wall height 880mm.

This declares that the stated product range complies with the highest requirements of the
European standard BSEN 771-3:2011

This declaration is awarded the following tests carried out on samples on the stated product range.

Essential Requirements	Declared Performance	Technical specification
Dimensional tolerances	D2	EN 771-5.2.2.1
Compressive Strength	>40Nmm ²	EN771-3 5.5.1.1
Configuration	Solid and void	En1996-1 1 (ec6)
Durability	Satisfactory for purpose	
Reaction to fire	Class A1	EN13501-1
Emission of Asbestos	None	
Gross dry density	2161kg/m ³	EN 771-3
Dangerous Substances	None	
Note: Refer to the Tobermore Paving & Walling Specification Guide for comprehensive product details		

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the above Standard when installed in accordance with Tobermore's guidelines

Signed: 

Full Name: David Henderson
Position: Owner & Managing
Director, Tobermore
Date: January 2024

This declaration is the responsibility of the manufacturer:
Tobermore Head Office
2 Lisnamuck Road, Tobermore, County L'derry, BT45 5QF
Tel: NI: 028 7964 2411 | GB: 0844 800 5736