

Chieftain VS5

large format paving

- Shift protection on five sides of the block provides maximum stability
- Granite appearance
- Manufactured with natural granite aggregates
- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Creates a striking, contemporary look

Other versions available:



product specifications

Product type	Concrete Paving Block
Manufactured to	BS EN 1339:2003
Surface Layer	Hard wearing surface layer with a minimum of 4mm and >350kg/m ³ cement
Surface Finish	Textured Granite Aggregate
Granite Content	Not less than 53% of granite aggregate in surface layer for Silver, Mid Grey, Graphite; Not less than 45% of granite aggregate in surface layer for Sandstone.
Spacer	Unique VS5 spacer which adds shift protection on five sides of the block
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Typical tensile splitting strength of >3.5MPa
Slip/Skid risk	Extremely Low
Installed to	Specific installation instructions for Chieftain are available from Tobermore
NSI	Plus: Q25 315 Create: 45-20-64/395
Applications	<p>800x400x100mm & 1200x400x120mm: Suitable for pedestrianised areas. Technical guidance must be considered for any other application. The latest British Standard should be consulted to ensure the correct sub-base design is achieved prior to installation. Specialised design advice can be obtained by contacting Tobermore directly.</p> <p>800x400x120mm: Suitable for pedestrianised areas or areas with occasional vehicular traffic overrun. Technical guidance must be considered for any other application. The latest British Standard should be consulted to ensure the correct sub-base design is achieved prior to installation. Specialised design advice can be obtained by contacting Tobermore directly.</p>
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 6% (all colours except Sandstone)
Carbon Footprint	<p>100mm: Silver: 40kgCo²e/m² Mid Grey: 43kgCo²e/m² Sandstone: 43kgCo²e/m² Graphite: 43kgCo²e/m²</p> <p>120mm: Silver: 48kgCo²e/m² Mid Grey: 51kgCo²e/m² Sandstone: 51kgCo²e/m² Graphite: 51kgCo²e/m²</p>
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breedam rating www.bre.co.uk	Refer to the Green Guide to Specification, 4 th Edition 2009
Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO 14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016 and BES 6001.	

colours



Important Information

Light coloured blocks emphasise tyre marks and oil spills. It must be accepted that these products will need more maintenance if the overall appearance is to be maintained.



Chieftain VS5 Graphite



product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight (kg) per pack
CHIEFTAIN VS5 BIM	800 x 400 x 100	Graphite, Mid Grey, Sandstone, Silver	SPECIAL ORDER	5.12	0.64	3.125	16	1156
	800 x 400 x 120	Graphite, Mid Grey, Sandstone, Silver	SPECIAL ORDER	4.48	0.64	3.125	14	1214
	1200 x 400 x 120	Graphite, Mid Grey, Sandstone, Silver	SPECIAL ORDER	5.76	0.96	2.08	12	1552

BIM This product is available to download from our website in BIM Level 2 format.

Refer to all instructions and warnings on our website