

Pavo

Manhattan Constellation

600 x 150 x 80 / 500 x 125 x 140

Manhattan Pavo will transform any project into a modern oasis.

The three-way mix of graphite, mid-grey and silver, using this unique linear product will create stunning and unique spaces for any commercial project. This sleek design is sure to impress.




SCAN HERE



80mm

Depth


1. Silver



2. Mid Grey





3. Graphite



Specification

Product type	Concrete Paving
Manufactured to	BS EN 1338:2003 & BS EN 1339:2003
Surface Layer	Hard-wearing surface layer with a minimum of 4mm and >350kgs/m ³ cement
Surface Finish	Textured Granite Aggregate
Granite Content	Not less than 53% of granite aggregate in surface layer for Silver, Mid Grey and Graphite; Not less than 45% of granite aggregate in surface layer for Sandstone
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	BS EN 1338:2003 Typical tensile splitting strength of >3.6MPa, BS EN 1339:2003 Typical tensile splitting strength of >5MPa (Class 3)
Slip/Skid resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45
Installed to	Latest version of BS 7533
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance	≤ 23mm (Wide Wheel Abrasion Test) - Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m ² as a mean with no individual value >1.5kg/m ² - Class 3
External Fire Performance	Deemed to satisfy. See Commission Decision 2000/553/EC
Reaction to fire	Class A1
Applications	600x150x80mm with a correctly designed sub-base is suitable for pedestrians and residential driveways.
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 6%
 Carbon Footprint	EPD Verified (2020) 600x150x80mm - 23.47kgCO₂e/m²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
 Breeam rating www.bre.co.uk	Refer to the Green Guide to Specification, latest edition
Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.	

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Manhattan Pavo	600 x 150 x 80	Graphite, Mid Grey & Silver Pavo Mix	YES	9.6	1.6	50	480	1756	1746
	500 x 125 x 140								