

Hydropave Textured Flags

beautiful granular surface

- Functions as a SuDS paving system
- Superb hard-wearing textured surface
- Vibrant long-lasting colours
- Natural appearance

product specifications

Product type	Concrete Paving Flag
Manufactured to	BS EN 1339:2003
Surface layer	Hard wearing surface layer with a minimum of 4mm and >390kgs/m ³ cement
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Frost Protection	Yes
Drainage Void Width	2.7% to accommodate correct grit grading, reduced maintenance and maximise drainage flow rate
Permeability	15,000 litres/sec/hectare
Strength	Less than 50mm deep >3.5MPa Greater than 50mm deep >5MPa (Class 3)
Slip/Skid risk	Extremely Low
Installed to	BS 7533-4:2006
BS5	Plus: Q25 315 Create: 45-20-64/395
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 6%
Carbon Footprint	28kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016 and BES 6001.



FM 11763 EMS 88400

colours



Textured Flags Natural (for colour reference only)



Tobermore's unique interlocking nib system enhances permeability and structural integrity.

product	size (mm)	finish	edge	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight (kg) per pack
HYDROPAVE TEXTURED FLAGS	400 x 400 x 65	TEXTURED	CHAMFERED	Charcoal, Natural	SPECIAL ORDER	10.56	3.52	6.25	66	1546

Refer to all instructions and warnings on our website