

Marker Block



SCAN HERE

Coloured indicator.

Marker Blocks offer a high-performance high-visibility marking solution. Coated in exceptionally hard-wearing pigments they eliminate the need for painting.

- Cost-effective solution where high visibility road markings are required
- Suitable for delineation & signage
- Coated with exceptionally hard-wearing heavy pigments
- Coloured marker eliminating the need for painting

 **PrimeTop®**

 **Ef-Stop®**



Finish



Also available as



Pedestrian
Use



Light
Traffic



Commercial
Traffic

Refer to relevant guidance in BS 7533



200 x 100mm



240 x 120mm

Sizes



50mm

60mm

80mm

Depths





Marker Block



Specification




Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Surface Finish	Painted
Chamfer	Standard
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Tensile Splitting Strength	Characteristic tensile splitting strength not less than 3.6 MPa
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45
Installed to	BS 7533-3:2005
NS	Plus Q24 110 Create 45-20-64/400
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m ² as a mean with no individual value > 1.5 kg/m ² Class 3
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to Fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 12%
 Carbon Footprint	EPD Verified (2020) 21.58kgCO ₂ e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
 Breeam rating www.bre.co.uk	B , according to the Green Guide to Specification, 4 th Edition 2009. A , can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.


Stock

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Marker Block	200 x 100 x 80	Black, Green, White, Yellow	YES	9.6	1.6	50	480	1724	1714
Hydropave Marker Block	200 x 100 x 60	White	YES	13.4	2.24	50	672	1808	1798
	200 x 100 x 80	Green, Yellow, White	YES	9.6	1.6	50	480	1732	1722
	240 x 120 x 80	Green, White	YES	10.1	2.02	34.7	350	1810	1800

White



Black



Yellow



Green



Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk