



Retro

Classic European styling.

Retro block paving is reminiscent of the paved streets and plazas of Northern Europe and is the ideal paving to add character to a traditional scheme. Its slender shape and textured aged surface is particularly suited to more intimate spaces in addition to expansive use.

- Processed to give an aged, antique appearance
- Vibrant long-lasting colours
- Suitable for both modern or traditional projects
- Creates a vintage, cobbled look
- Option to lay textured side up, smooth side up or mixed



Sizes



60mr

Depths

Ef-Stop®









Refer to relevant guidance in BS 7533





Retro



Specification ▼ Ef-Stop°

	<u> </u>
Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Manufacturing process	Processed to give aged appearance
Chamfer	Processed to give aged appearance
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Tensile Splitting Strength	Characteristic tensile splitting strength not less than 3.6 MPa
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45
	Mean unpolished skid resistance value (USRV) > 45
Installed to	BS 7533-3:2005
กรร	Plus Q24 110 Create 45-20-64/400
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m² Class 3
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to Fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 10%
Carbon Footprint	EPD Verified (2020) 16.50kgCo²e/m²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
www.bre.co.uk	A, according to the Green Guide to Specification, 4th Edition 2009. A+, can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:1026 and BES 6001.

Stock

ŗ	product	size (mm)	colours available	in stock	m² per pack	m² per slice	no. per m²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
	Retro	190 x 50 x 60	Bracken, Heather, Slate	YES	6.5	2 or 4	105.3	684	820	810

Heather



Bracken



Slate



IMPORTANT INFORMATION

Please note that Retro has both a textured and a smooth surface, either can be laid upwards as the paving surface. It is important that laying instructions state clearly:

- Textured surface up
 Smooth surface up
- Mixed Smooth and Textured surfaces up