

Sienna Setts




SCAN HERE

Attractive borders and features.

Sienna Setts are crafted with natural granite aggregates for a vibrant granite appearance.

- Manufactured with natural granite aggregates
- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Creates a striking, contemporary look



50mm

Depths

 **PrimeTop®**  **Ef-Stop®**

TGA

Textured
Granite Aggregate

Finish



Pedestrian
Use



Light
Traffic

Refer to relevant guidance in BS 7533





Sienna Setts



Specification

 **PrimeTop®**  **Ef-Stop®**

Product type	Concrete Paving Block		
Manufactured to	BS EN 1338:2003		
Surface Layer	Hard-wearing surface layer with a minimum of 4mm and >350kgs/m ³ cement		
Surface Finish	Textured Granite Aggregate		
Granite Content	Not less than 53% of granite aggregate in surface layer for Silver and Graphite; Not less than 45% of granite aggregate in surface layer for Oat		
Chamfer	Square Edged		
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence		
Tensile Splitting Strength	Characteristic tensile splitting strength not less than 3.6 MPa		
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45		
Installed to	BS 7533-3:2005		
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm		
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3		
Durability (Freeze-thaw)	≤ 1.0 kg/m ² as a mean with no individual value > 1.5 kg/m ² Class 3		
External Fire Performance	Deemed to satisfy when used for roofing		
Reaction to Fire	Class A1		
BS	Plus Q24 110 Create 45-20-64/410		
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com		
Energy used	100% renewable energy		
Water used	100% from our rainwater harvesting system and groundwater bore hole		
Recycled content	Not less than 6%		
 Carbon Footprint	EPD Verified (2020) 50mm	Silver Oat Graphite	20kgCo ² e/m ² 22kgCo ² e/m ² 22kgCo ² e/m ²
Recyclable	100% of this product can be recycled		
Manufacturing & Delivery	From one location within the UK		
 Breeam rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved when used in conjunction with a prepared recycled sub-base.		

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk

Sienna Setts



Stock

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Sienna Setts	100 x 100 x 50	Graphite, Oat, Silver	YES	11.52	0.96	100	1152	1336	1335

Silver



Oat



Graphite



IMPORTANT INFORMATION

Tobermore recommend that you separate product groups using contrasting bands of colour as each product is manufactured separately and may have slight variations in colour.

Inevitably on light coloured units any contamination caused by vehicle tyres, leaves, beverages / food etc will be more visible compared to darker coloured units. Therefore careful consideration should be applied when specifying colours in

specific applications. If light coloured units are specified it must be accepted that these will require more maintenance if the overall appearance is to be maintained.

Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk