

Textured Flags



SCAN HERE

Stylish granular surface.

Textured Flags have a modern and natural look that blends beautifully with a variety of other products. Manufactured with a hard-wearing granular surface, these flags are both stylish and hard-wearing.

- Superb hard-wearing textured surface
- Vibrant long-lasting colours
- Natural appearance

 **PrimeTop®**  **Ef-Stop®**



Finish



Also available as



Pedestrian
Use



Light
Traffic




Commercial
Traffic



BIM
Level 2


Refer to relevant guidance in BS 7533




600 x 600mm



600 x 400mm



450 x 450mm



400 x 400mm

Sizes



32mm
35mm
40mm
50mm

Depths





Textured Flags



Specification

 **PrimeTop®**  **Ef-Stop®**

Product type	Concrete Paving Flag
Manufactured to	BS EN 1339:2003
Surface Layer	Hard-wearing surface layer with a minimum of 4mm and >390kgs/m ³ cement
Chamfer	Chamfered
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Bending Strength	Less than 50mm deep Characteristic tensile splitting strength not less than 3.6 MPa 50mm or greater Characteristic tensile splitting strength of >5MPa (Class 3)
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45
Installed to	BS 7533-4:2006
NS	Plus Q25 315 Create 45-20-64/395
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m ² as a mean with no individual value > 1.5 kg/m ² Class 3
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
 Carbon Footprint	EPD Verified (2020) 400x400x32mm 8.09kgCo ² e/m ² 400x400x40mm 9.06kgCo ² e/m ² 450x450x35mm 8.72kgCo ² e/m ² 450x450x50mm 12.08kgCo ² e/m ² 600x600x40mm 9.96kgCo ² e/m ² 600x600x50mm 12.09kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
 breem rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk

Textured Flags



Stock


product	size (mm)	edge	colours available	in stock	no. per m ²	no. per pack	no. per pallet	weight kg per pack GB	weight kg per pack NI/ROI
Textured Flags BIM	600 x 600 x 50	Chamfered	Buff, Charcoal, Natural	YES	2.78	20	20	850	842
	600 x 600 x 40	Chamfered	Buff, Charcoal, Natural	YES	2.78	24	24	848	840
	600 x 400 x 40	Chamfered	Charcoal, Natural	YES	4.16	25	50	569	560
	450 x 450 x 50	Chamfered	Buff, Charcoal, Natural	YES	4.94	20	80	1490	1480
	450 x 450 x 35	Chamfered	Buff, Charcoal, Natural	YES	4.94	30	120	521	517
	400 x 400 x 40	Chamfered	Charcoal, Golden, Natural	YES	6.25	25	100	403	400
	400 x 400 x 32	Chamfered	Charcoal, Golden, Natural	YES	6.25	30	120	387	385

BIM - This product is available to download from our website in BIM Level 2 format.


Natural



Charcoal



Buff



Golden



Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk