

# Turfstone



SCAN HERE


## Grass paving system.

Turfstone is a ground reinforcement grass paving system ideal for occasional car parking or emergency vehicle access where the addition of grass is an attractive feature. The honeycombed cavities are designed to facilitate the growth of grass.

- Honey-combed cavities are designed to facilitate the growth of grass
- Functions as a SuDS permeable pavement

### Turfstone typical applications:

- Vehicular access for occasional usage (emergency vehicle and utility access)
- Overspill car parking with infrequent trafficking (sports clubs, cemeteries, caravan parks)
- Nature reserves, sensitive heritage sites and country parks
- Road verges
- Environmental erosion control areas such as riverbanks and waterways
- Field entrances and farm tracks
- SuDS schemes



600 x 400mm

### Sizes



100mm

### Depths

## Ef-Stop®

ST

Standard

Finish



Pedestrian Use



Light Traffic



Commercial Traffic

Refer to relevant guidance in BS 7533



# Turfstone



## Specification



<b>Product type</b>	Concrete Paving Block
<b>Manufactured to</b>	BS EN 771-3: 2011
<b>Surface Finish</b>	Standard
<b>Efflorescence</b>	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
<b>Strength</b>	Typical tensile splitting strength of >5MPa (Class 3)
<b>Slip/Skid risk</b>	Extremely Low
<b>Installed to</b>	Specific installation guidelines are available from Tobermore
<b>BSI</b>	<b>Plus</b> Q25 345 <b>Create</b> 45-20-64/390
<b>Applications</b>	Refer to the relevant part of BS 7533 for the correct sub-base design for your application. Available from <a href="http://www.bsigroup.com">www.bsigroup.com</a>
<b>Energy used</b>	100% renewable energy
<b>Water used</b>	100% from our rainwater harvesting system and groundwater bore hole
<b>Recycled content</b>	Not less than 5%
<b>Carbon Footprint</b>	24kgCo <sup>2</sup> e/m <sup>2</sup>
<b>Recyclable</b>	100% of this product can be recycled
<b>Manufacturing &amp; Delivery</b>	From one location within the UK
<b>breeam rating</b> <a href="http://www.bre.co.uk">www.bre.co.uk</a>	Refer to the Green Guide to Specification, 4 <sup>th</sup> Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:1026 and BES 6001.

## Stock

product	size (mm)	colours available	in stock	m <sup>2</sup> per pack	m <sup>2</sup> per slice	no. per m <sup>2</sup>	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
<b>Turfstone</b>	600 x 400 x 100	Natural	Yes	7.68	3.84	4.17	32	1070	1060

### Contact Us

GB: 0844 800 5736  
 NI: 028 7964 2411  
 ROI: 048 7964 2411

### Email

[technical@tobermore.co.uk](mailto:technical@tobermore.co.uk)  
[sales@tobermore.co.uk](mailto:sales@tobermore.co.uk)

[tobermore.co.uk](http://tobermore.co.uk)