

# Turfstone

ground reinforcement grass paving system

- Honey-combed cavities are designed to facilitate the growth of grass
- Functions as a SuDS permeable pavement
- Cost-effective alternative

## product specifications

<b>Product type</b>	Concrete Paving Block
<b>Manufactured to</b>	BS EN 1338:2003
<b>Surface Finish</b>	Standard
<b>Efflorescence</b>	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
<b>Strength</b>	Typical tensile splitting strength of >3.5MPa
<b>Slip/Skid risk</b>	Extremely Low
<b>Installed to</b>	BS 7533-3:2005
<b>BS</b>	<b>Plus:</b> Q25 345 <b>Create:</b> 45-20-64/390
<b>Applications</b>	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from <a href="http://www.bsigroup.com">www.bsigroup.com</a>
<b>Energy used</b>	100% renewable energy
<b>Water used</b>	100% from our rainwater harvesting system and groundwater bore hole
<b>Recycled content</b>	Not less than 5%
<b>Carbon Footprint</b>	24kgCO <sub>2</sub> e/m <sup>2</sup>
<b>Recyclable</b>	100% of this product can be recycled
<b>Manufacturing &amp; Delivery</b>	From one location within the UK
<b>breem rating</b> <a href="http://www.bre.co.uk">www.bre.co.uk</a>	Refer to the Green Guide to Specification, 4 <sup>th</sup> Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016 and BES 6001.



## Typical uses include:

- Off-street residential parking
- Vehicular access for occasional usage i.e. fire tender and utility access
- Overspill commercial or retail parking
- Occasional parking for cricket clubs, schools, churches, caravan parks, cemeteries etc.
- Nature reserves, sensitive heritage sites and country parks
- Environmental erosion control areas such as riverbanks and waterways
- Road verges
- Field entrances and farm tracks
- SuDS schemes

For installation guidelines refer to our website or contact the Tobermore Sales Office.

## colours



Turfstone Natural

product	size (mm)	colours available	in stock	m <sup>2</sup> per pack	m <sup>2</sup> per slice	no. per m <sup>2</sup>	no. per pack	weight (kg) per pack
TURFSTONE	600 x 400 x 100	Natural	YES	7.68	3.84	4.17	32	1060

Refer to all instructions and warnings on our website